



Air Conditioning & Heating



## PRODUCT SPECIFICATIONS

# GSC13

## 13 SEER

HIGH-EFFICIENCY  
SPLIT SYSTEM  
AIR CONDITIONER

### 1½ TO 5 TON



The GSC13 Split System Air Conditioner features the unique Goodman® sound control top designed for quiet operation.

#### Standard Features

- Energy-efficiency compressor
- Copper tube/aluminum fin coil
- R-22 refrigerant-charged for 15' of refrigerant lines
- Factory-installed liquid line filter dryer
- Brass liquid and suction service valves with sweat connections
- Contactor with lug connections
- Ground lug connection
- ARI Certified
- ETL Certified

#### Cabinet Features

- Unique Goodman® sound control top design
- Steel louver coil guard
- Heavy-gauge galvanized-steel cabinet
- Attractive Architectural Gray powder-paint finish with 500-hour salt-spray approval
- When properly anchored, meets the 2001 Florida Building Code unit integrity requirements for hurricane-type winds

#### Air Handler and Coil Compatibilities

- ARPF/ARPT, ADPF, ARUF, AEPF/AEPT – versatile upflow, horizontal or downflow air handlers; may be located in closets, utility rooms, attics, or basements
- AWUF/AWB vertical wall-mounted electric heat air handlers
- ACNF/AC ceiling-mounted electric heat air handlers
- MBR/MBE modular blower
- CA, CH, and CSCF indoor coils


#### Accessories

- Standard room thermostat with 1-stage cool/1-stage heat
- Digital room thermostat with 1-stage cool/1-stage heat
- Outdoor thermostat
- High- and low-pressure switch kit
- Low-pressure switch kit
- Low ambient kit



# PRODUCT SPECIFICATIONS

## NOMENCLATURE



## ACCESSORIES

Model	Description	GSC13 018	GSC13 024	GSC13 030	GSC13 036	GSC13 042	GSC13 048	GSC13 060
ASC01	Anti-Short Cycle Kit	X	X	X	X	X	X	X
CSR-U-1	Hard-start Kit	X	X	X	X			
CSR-U-2	Hard-start Kit				X	X	X	X
CSR-U-3	Hard-start Kit						X	X
FSK01A <sup>1</sup>	Freeze Protection Kit	X	X	X	X	X	X	X
LSK01A <sup>2</sup>	Liquid Line Solenoid Kit	X	X	X	X	X	X	X
OT18-60A	Outdoor Thermostat	X	X	X	X	X	X	X
TX3N2 <sup>2</sup>	TXV Kit -- Field-installed, non-bleed expansion valve kit	X	X	X	X			
TX5N2 <sup>2</sup>	TXV Kit -- Field-installed, non-bleed expansion valve kit					X	X	X

<sup>1</sup> Installed on indoor coil

<sup>2</sup> Condensing units and heat pumps with reciprocating compressors require the use of start-assist components when used in conjunction with an indoor coil using a non-bleed thermal expansion valve refrigerant metering device or liquid line solenoid kit.

## SPECIFICATIONS

	GSC13-0181AA	GSC13-0241A	GSC13-0241C	GSC13-0301A	GSC13-0361A	GSC13-0361B	GSC13-0361C
<b>Cooling Capacities</b>							
Nominal Cooling (BTU/h)	18,000	24000	24,000	30,000	36,000	36,000	36,000
Decibels	76	76	76	76	76	76	76
<b>Compressor</b>							
RLA	6.2	7.7	10.4	9.7	12.2	12.5	11.2
LRA	35.0	40.0	54.0	49.0	73.0	73.0	68.0
<b>Condenser Fan Motor</b>							
Horsepower	1/6	1/6	1/6	1/6	1/6	1/6	1/6
FLA	1.5	1.5	1.5	1.5	1.5	1.5	1.5
<b>Refrigeration System</b>							
Liquid Valve Size ("O.D.)	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"
Suction Valve Size ("O.D.)	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"
Valve Type	Sweat	Sweat	Sweat	Sweat	Sweat	Sweat	Sweat
Refrigerant Charge	95	99	102	123	125	125	120
Shipped with Orifice Size	0.055	0.059	0.059	0.065	0.074	0.071	0.074
<b>Electrical Data</b>							
AC Volts	208/230	208/230	208/230	208/230	208/230	208/230	208/230
Hz / Phase	60 Hz/1	60 Hz/1	60 Hz/1	60 Hz/1	60 Hz/1	60 Hz/1	60 Hz/1
Min. Circuit Ampacity <sup>1</sup>	9.3	11.2	14.6	13.6	16.8	17.1	15.5
Max. Overcurrent Device <sup>2</sup>	15	15	20	20	20	20	20
Min / Max Volts	197/253	197/253	197/253	197/253	197/253	197/253	197/253
Electrical Conduit Size	1/2" or 3/4"	1/2" or 3/4"	1/2" or 3/4"	1/2" or 3/4"	1/2" or 3/4"	1/2" or 3/4"	1/2" or 3/4"
Ship Weight (lbs)	173	195	182	195	199	205	214

<sup>1</sup> Wire size should be determined in accordance with National Electrical Codes; extensive wire runs will require larger wire sizes

<sup>2</sup> Must use time-delay fuses or HACR-type circuit breakers of the same size as noted

# PRODUCT SPECIFICATIONS


## SPECIFICATIONS (CONT.)

	GSC13 0363A	GSC13 0421A	GSC13 0481A	GSC13 0483A	GSC13 0484A	GSC13 0601B	GSC13 0603A	GSC13 0604A
<b>Cooling Capacities</b>								
Nominal Cooling (BTU/h)	36,000	42,000	48,000	48,000	48,000	57,000	57,000	57,000
Decibels	76	76	76	76	76	76	76	76
<b>Compressor</b>								
RLA	9.0	14.7	17.9	12.4	5.8	25.0	17.3	6.7
LRA	65.5	77.0	104.0	88.0	44.0	148.0	123.0	49.5
<b>Condenser Fan Motor</b>								
Horsepower	1/6	¼	¼	¼	¼	1/6	1/6	1/6
FLA	1.5	1.6	1.6	1.6	0.8	1.1	1.1	0.6
<b>Refrigeration System</b>								
Liquid Valve Size ("O.D.)	⅜"	⅜"	⅜"	⅜"	⅜"	⅜"	⅜"	⅜"
Suction Valve Size ("O.D.)	¾"	⅞"	⅞"	⅞"	⅞"	⅞"	⅞"	⅞"
Valve Type	Sweat	Sweat	Sweat	Sweat	Sweat	Sweat	Sweat	Sweat
Refrigerant Charge	125	143	158	158	158	175	175	175
Shipped with Orifice Size	0.074	0.078	0.082	0.082	0.082	0.093	0.093	0.093
<b>Electrical Data</b>								
AC Volts	208/230	208/230	208/230	208/230	460	208/230	208/230	460
Hz / Phase	60 Hz/3	60 Hz/1	60 Hz/1	60 Hz/3	60 Hz/3	60 Hz/1	60 Hz/3	60 Hz/3
Min. Circuit Ampacity <sup>1</sup>	12.7	20	24	17.2	8.0	32.3	22.7	9.0
Max. Overcurrent Device <sup>2</sup>	20	30	40	20	15	50	40	15
Min / Max Volts	197/253	197/253	197/253	197/253	414/506	197/253	197/253	414/506
Electrical Conduit Size	½" or ¾"	½" or ¾"	½" or ¾"	½" or ¾"	½" or ¾"	½" or ¾"	½" or ¾"	½" or ¾"
Ship Weight (lbs)	198	199	207	207	207	242	242	242

<sup>1</sup> Wire size should be determined in accordance with National Electrical Codes; extensive wire runs will require larger wire sizes

<sup>2</sup> Must use time-delay fuses or HACR-type circuit breakers of the same size as noted

DIMENSIONS



Model	Dimensions W" x D" x H"
GSC130181A	26 x 26 x 29 <sup>3</sup> / <sub>4</sub>
GSC130241A	26 x 26 x 34 <sup>3</sup> / <sub>4</sub>
GSC130241C	26 x 26 x 34 <sup>3</sup> / <sub>4</sub>
GSC130301A	29 x 29 x 34 <sup>3</sup> / <sub>4</sub>
GSC130361A	29 x 29 x 34 <sup>1</sup> / <sub>4</sub>
GSC130361B	29 x 29 x 34 <sup>3</sup> / <sub>4</sub>
GSC130361C	29 x 29 x 34 <sup>3</sup> / <sub>4</sub>
GSC130363A	29 x 29 x 34 <sup>1</sup> / <sub>4</sub>
GSC130421A	29 x 29 x 34 <sup>1</sup> / <sub>4</sub>
GSC130481A	29 x 29 x 38 <sup>1</sup> / <sub>4</sub>
GSC130483A	29 x 29 x 38 <sup>1</sup> / <sub>4</sub>
GSC130484A	29 x 29 x 38 <sup>1</sup> / <sub>4</sub>
GSC130601B	35 <sup>1</sup> / <sub>2</sub> x 35 <sup>1</sup> / <sub>2</sub> x 38 <sup>1</sup> / <sub>4</sub>
GSC130603A	35 <sup>1</sup> / <sub>2</sub> x 35 <sup>1</sup> / <sub>2</sub> x 38 <sup>1</sup> / <sub>4</sub>
GSC130604A	35 <sup>1</sup> / <sub>2</sub> x 35 <sup>1</sup> / <sub>2</sub> x 38 <sup>1</sup> / <sub>4</sub>

# PRODUCT SPECIFICATIONS

## PERFORMANCE RATINGS

Outdoor Unit	Indoor Unit	Cooling Capacity				ARI Ref #
		Total	Sensible	SEER <sup>1</sup>	EER <sup>2</sup>	
GSC13 0181A*	AC18-XX	18,000	12,780	13	11.5	728986
	ACNF018-XX1A*	18,000	12,780	13	11.5	728989
	ADPF182416A*	19,000	13,490	13	11.5	1038100
	ADPF18241A*	19,000	13,490	13	11.5	1038136
	ADPF18241B*	19,000	13,490	13	11.5	1062382
	AEPF183016A*	19,000	13,490	14	12	1038101
	AEPF18301A*	19,000	13,490	14	12	734461
	AEPF18301B*	19,000	13,490	14	12	1062383
	AEPT030-00*-1*	19,000	13,490	14	12	734428
	ARPF036-00B-1*	19,000	13,490	13	11.5	734445
	ARPF182416A*	19,000	13,490	13	11.5	1038102
	ARPF18241A*	19,000	13,490	13	11.5	734443
	ARPF18241B*	19,000	13,490	13	11.5	1062384
	ARPT032-00*-1*	19,000	13,490	13	11.5	734466
	ARUF032-00*-1*	19,000	13,490	13	11.5	734435
	ARUF182416A*	19,000	13,490	13	11.5	1038103
	ARUF18241A*	19,000	13,490	13	11.5	734444
	ARUF18241B*	19,000	13,490	13	11.5	1062385
	AWB24-XX	18,000	12,780	13	11.5	728988
	AWUF18XX1A*	18,000	12,780	13	11.5	728987
	CA*F030*2*+EEP	19,000	13,490	13	11.5	734419
	CA*F030*2*+G*V80704B**	19,000	13,490	14	12	734458
	CA*F030*2*+G*V90704C**	19,000	13,490	14	12	734433
	CA*F030*2*+G*V950453B**	19,000	13,490	14	12	734421
	CA*F030*2*+MBE1200	19,000	13,490	14	12	734423
	CA*F1824*6A*+EEP	19,000	13,490	13	11.5	734464
	CA*F1824*6A*+G*V80704B**	19,000	13,490	14	12	734425
	CA*F1824*6A*+G*V90704C**	19,000	13,490	14	12	734462
	CA*F1824*6A*+G*V950453B**	19,000	13,490	14	12	734460
	CA*F1824*6A*+G*V950704C**	19,000	13,490	14	12	734451
	CA*F1824*6A+MBE1200	19,000	13,490	14	12	734447
	CA*F3030*6A*+G*V950704C**	19,000	13,490	14	12	734456
	CHPF030A2*+EEP	19,000	13,490	13	11.5	734465
	CHPF036B2*+EEP+TXV	18,000	12,780	13	11.5	1069406
	CHPF042B2*+EEP	19,000	13,490	13	11.5	879223
	CHPF042B2*+G*V80704B**	19,600	13,916	14	12	734427
	CHPF042B2*+G*V90704C**	19,600	13,916	14	12	734420
	CHPF042B2*+G*V950453B**	19,600	13,916	14	12	734437
	CHPF1824A6A*+EEP	19,000	13,490	13	11.5	734429
	CHPF2430B6A*+EEP	19,000	13,490	13	11.5	879233
	CHPF2430B6A*+G*V80704B**	19,600	13,916	14	12	734439
	CHPF2430B6A*+G*V90704C**	19,600	13,916	14	12	734432
	CHPF2430B6A*+G*V950453B**	19,600	13,916	14	12	736261
CSCF1824N6A*+EEP	19,000	13,490	13	11.5	734440	
CSCF1824N6A*+G*V80704B**	19,000	13,490	14	12	734441	
CSCF1824N6A*+G*V90704C**	19,000	13,490	14	12	734457	
CSCF1824N6A*+G*V950453B**	19,000	13,490	14	12	736247	
H36F+EEP	19,000	13,490	13	11.5	734422	
H36F+G*V80704B**	19,000	13,490	14	12	734430	
H36F+G*V90704C**	19,000	13,490	14	12	734448	
H36F+G*V950453B**	19,000	13,490	14	12	734424	

<sup>1</sup> Seasonal Energy Efficiency Ratio

<sup>2</sup> Energy Efficiency Ratio @ 80 °F/67 °F Inside - 95 °F

Notes:

- When matching the outdoor unit to the indoor unit, use the piston supplied with the outdoor unit or that specified on the piston kit chart supplied with the indoor unit.
- XX of a model designates Electric Heat kilowatts.
- EEP: Order from Service Dept. Part No. B13707-38 or new Solid State Board B13707-35S. Part No. B13707-38 is not interchangeable with B13707-35S. The Goodman Gas Furnace contains the EEP cooling time delay.

PERFORMANCE RATINGS (CONT.)

Outdoor Unit	Indoor Unit	Cooling Capacity				ARI Ref #
		Total	Sensible	SEER <sup>1</sup>	EER <sup>2</sup>	
GSC13 0241C*	AC30-XX	23,000	16,330	13	11.5	734463
	ACNF24XX1A*	23,000	16,330	13	11.5	734459
	ADPF182416A*	23,000	16,330	13	11.5	1038104
	ADPF18241A*	23,000	16,330	13	11.5	1038137
	ADPF18241B*	23,000	16,330	13	11.5	1062386
	AEPF183016A*	23,800	16,898	14	11.5	1038105
	AEPF18301A*	23,800	16,898	14	11.5	734436
	AEPF18301B*	23,800	16,898	14	12	1062387
	AEPT030-00*-1*	23,800	16,898	14	11.5	734426
	ARPF036-00B-1*	23,000	16,330	13	11.5	734431
	ARPF182416A*	23,000	16,330	13	11.5	1038106
	ARPF18241A*	23,000	16,330	13	11.5	734438
	ARPF18241B*	23,000	16,330	13	11.5	1062388
	ARPT032-00*-1*	23,000	16,330	13	11.5	734450
	ARUF032-00*-1*	23,000	16,330	13	11.5	734442
	ARUF182416A*	23,000	16,330	13	11.5	1038107
	ARUF18241A*	23,000	16,330	13	11.5	734434
	ARUF18241B*	23,000	16,330	13	11.5	1062389
	AWB24-XX	23,000	16,330	13	11.5	734452
	AWUF24XX1A*	23,000	16,330	13	11.5	734455
	CA*F030*2*+EEP	23,000	16,330	13	11.5	734449
	CA*F030*2*+G*V80704B**	23,000	16,330	14	12	734664
	CA*F030*2*+G*V90704C**	23,000	16,330	14	12	734803
	CA*F030*2*+G*V950453B**	23,000	16,330	14	12	734884
	CA*F030*2*+G*V950704C**	23,000	16,330	14	12	734821
	CA*F030*2*+MBE1200	23,000	16,330	14	12	734802
	CA*F1824*6A*+EEP	23,000	16,330	13	11.5	734453
	CA*F1824*6A*+G*V80704B**	23,000	16,330	14	12	734742
	CA*F1824*6A*+G*V90704C**	23,000	16,330	14	12	734806
	CA*F1824*6A*+G*V950453B**	23,000	16,330	14	12	734660
	CA*F1824*6A*+G*V950704C**	23,000	16,330	14	12	734848
	CA*F1824*6A*+MBE1200	23,000	16,330	14	12	734705
	CHPF030A2*+EEP	23,000	16,330	13	11.5	734736
	CHPF036B2*+EEP+TXV	21,000	14,910	13	11.5	1069407
	CHPF042B2*+EEP	23,400	16,614	13	11.5	879222
	CHPF042B2*+G*V80704B**	23,800	16,898	14	12	734841
	CHPF042B2*+G*V90704C**	23,800	16,898	14	12	734657
	CHPF042B2*+G*V950453B**	23,800	16,898	14	12	734894
	CHPF1824A6A*+EEP	23,000	16,330	13	11.5	734744
	CHPF2430B6A*+EEP	23,400	16,614	13	11.5	879282
	CHPF2430B6A*+G*V80704B**	23,800	16,898	14	12	734836
	CHPF2430B6A*+G*V90704C**	23,800	16,898	14	12	734773
	CHPF2430B6A*+G*V950453B**	23,800	16,898	14	12	734656
	CSCF1824N6A*+EEP	23,000	16,330	13	11.5	734692
	CSCF1824N6A*+G*V80704B**	23,000	16,330	14	12	734818
CSCF1824N6A*+G*V90704C**	23,000	16,330	14	12	734775	
CSCF1824N6A*+G*V950453B**	23,000	16,330	14	12	734823	
H36F+EEP	23,000	16,330	13	11.5	734691	
H36F+G*V80704B**	23,000	16,330	14	12	734840	
H36F+G*V90704C**	23,000	16,330	14	12	734767	
H36F+G*V950453B**	23,000	16,330	14	12	734880	

<sup>1</sup> Seasonal Energy Efficiency Ratio

<sup>2</sup> Energy Efficiency Ratio @ 80 °F/67 °F Inside - 95 °F

See Notes on Page 6.

# PRODUCT SPECIFICATIONS

## PERFORMANCE RATINGS (CONT.)

Outdoor Unit	Indoor Unit	Cooling Capacity				ARI Ref #
		Total	Sensible	SEER <sup>1</sup>	EER <sup>2</sup>	
GSC13 0301A*	AC36-XX	28,000	20,720	13	11.5	734698
	ACNF30XX1A*	28,000	20,720	13	11.5	734815
	ADPF304216A*	29,000	21,460	13	11.5	1038108
	ADPF30421A*	29,000	21,460	13	11.5	734826
	ADPF30421B*	29,000	21,460	13	11.5	1062390
	AEPF183016A*	29,000	21,460	14	12	1038109
	AEPF18301A*	29,000	21,460	14	12	734732
	AEPF18301B*	29,000	21,460	14	12	1062391
	AEPT030-00*-1*	29,000	21,460	14	12	734714
	ARPF048-00B-1*	29,000	21,460	13	11.5	734798
	ARPF303016A*	29,000	21,460	13	11.5	1038110
	ARPF30301A*	29,000	21,460	13	11.5	734886
	ARPF30301B*	29,000	21,460	13	11.5	1062392
	ARPT042-00*-1*	29,000	21,460	13	11.5	734879
	ARUF042-00*-1*	29,000	21,460	13	11.5	734889
	ARUF182416A*	27,600	20,424	13	11.5	1038144
	ARUF18241A*	27,600	20,424	13	11.5	1038143
	ARUF18241B*	27,600	20,424	13	11.5	1062393
	ARUF303016A*	29,000	21,460	13	11.5	1038111
	ARUF30301A*	29,000	21,460	13	11.5	734784
	ARUF30301B*	29,000	21,460	13	11.5	1062394
	AWB36-XX	28,000	20,720	13	11.5	734873
	AWUF36XX1A*	28,000	20,720	13	11.5	734875
	CA*F037*2*+EEP	29,000	21,460	13	11.5	734718
	CA*F037*2*+G*V80704B**	29,000	21,460	14	12	734672
	CA*F037*2*+G*V90704C**	29,000	21,460	14	12	734651
	CA*F037*2*+G*V950453B**	29,000	21,460	14	12	734774
	CA*F037*2*+G*V950704C**	29,000	21,460	14	12	734902
	CA*F037*2*+MBE1200**-1	29,000	21,460	14	12	734687
	CA*F042*2*+EEP	29,000	21,460	13	11.5	879290
	CA*F3030*6A*+EEP	29,000	21,460	13	11.5	734671
	CA*F3030*6A*+G*V80704B**	29,000	21,460	14	12	734807
	CA*F3030*6A*+G*V90704C**	29,000	21,460	14	12	736252
	CA*F3030*6A*+G*V950453B**	29,000	21,460	14	12	734781
	CA*F3030*6A*+G*V950704C**	29,000	21,460	14	12	734724
	CA*F3030*6A*+MBE1200	29,000	21,460	14	12	734816
	CA*F3131*6A*+EEP	29,000	21,460	13	11.5	879204
	CHPF042B2*+EEP	29,000	21,460	13	11.5	734727
	CHPF042B2*+G*V80704B**	29,400	21,756	14	12	734801
	CHPF042B2*+G*V90704C**	29,400	21,756	14	12	734748
	CHPF042B2*+G*V950453B**	29,400	21,756	14	12	734726
	CHPF2430B6A*+EEP	29,000	21,460	13	11.5	734900
	CHPF2430B6A*+G*V80704B**	29,400	21,756	14	12	734888
	CHPF2430B6A*+G*V90704C**	29,400	21,756	14	12	734865
	CHPF2430B6A*+G*V950453B**	29,400	21,756	14	12	734666
	CHPF3636B6A*+EEP	29,000	21,460	13	11.5	1046066
	CSCF3036N6A*+EEP	29,000	21,460	13	11.5	734814
	CSCF3036N6A*+G*V80704B**	29,000	21,460	14	12	734809
	CSCF3036N6A*+G*V90704C**	29,000	21,460	14	12	734728
	CSCF3036N6A*+G*V950453B**	29,000	21,460	14	12	734794
H49F+EEP	29,000	21,460	13	11.5	734795	
H49F+G*V80704B**	29,000	21,460	14	12	734746	
H49F+G*V90704C**	29,000	21,460	14	12	734837	
H49F+G*V950453B**	29,000	21,460	14	12	734761	

<sup>1</sup> Seasonal Energy Efficiency Ratio

<sup>2</sup> Energy Efficiency Ratio @ 80 °F/67 °F Inside - 95 °F

See Notes on Page 6.

PERFORMANCE RATINGS (CONT.)

Outdoor Unit	Indoor Unit	Cooling Capacity				ARI Ref #
		Total	Sensible	SEER <sup>1</sup>	EER <sup>2</sup>	
GSC13 0361A*	ADPF304216A*	35,000	25,550	13	11.5	1038112
	ADPF30421A*	35,000	25,550	13	11.5	734661
	ADPF30421B*	35,000	25,550	13	11.5	1062395
	AEPF303616A*	35,000	25,550	14	12	1038113
	AEPF30361A*	35,000	25,550	14	12	734747
	AEPF30361B*	35,000	25,550	14	12	1062396
	AEPT036-00*-1*	35,000	25,550	14	12	734717
	ARPF048-00B-1*	35,000	25,550	13	11.5	734704
	ARPF364216A*	35,000	25,550	13	11.5	1038114
	ARPF36421A*	35,000	25,550	13	11.5	734842
	ARPF36421B*	35,000	25,550	13	11.5	1062397
	ARPT049-00*-1*	35,000	25,550	13	11.5	734693
	ARUF049-00*-1*	35,000	25,550	13	11.5	736539
	ARUF364216A*	33,600	24,528	13	11.5	1038115
	ARUF36421A*	35,000	25,550	13	11.5	736528
	ARUF36421B*	33,600	24,528	13	11.5	1062398
	AWB36-XX	33,600	24,528	13	11.5	734730
	AWUF36XX1A*	33,600	24,528	13	11.5	734799
	CA*F048*2*+EEP	35,000	25,550	13	11.5	734668
	CA*F048*2*+G*V80704B**	35,000	25,550	14	12	734680
	CA*F048*2*+G*V80905C**	35,000	25,550	14	12	734787
	CA*F048*2*+G*V90905D**	35,000	25,550	14	12	734819
	CA*F048*2*+G*V950905D**	35,000	25,550	14	12	734760
	CA*F048*2*+G*V951155D**	35,000	25,550	14	12	734856
	CA*F048*2*+MBE1600	35,000	25,550	14	12	734739
	CA*F3636*6A*+EEP	35,000	25,550	13	11.5	734824
	CA*F3636*6A*+G*V80704B**	35,000	25,550	14	12	734722
	CA*F3636*6A*+G*V80905C**	35,000	25,550	14	12	734891
	CA*F3636*6A*+G*V90403B**	35,000	25,550	13.5	11.8	1038380
	CA*F3636*6A*+G*V90905D**	35,000	25,550	14	12	734762
	CA*F3636*6A*+G*V950905D**	35,000	25,550	14	12	734876
	CA*F3636*6A*+G*V951155D**	35,000	25,550	14	12	734690
	CA*F3636*6A*+MBE1600	35,000	25,550	14	12	734846
	CA*F3642*6A*+EEP	35,000	25,550	13	11.5	1038152
	CHPF042B2*+EEP	34,000	24,820	13	11.5	1073255
	CHPF048D2*+EEP	35,000	25,550	13	11.5	734831
	CHPF048D2*+G*V80704B**	35,000	25,550	14	12	734887
	CHPF048D2*+G*V80905C**	35,000	25,550	14	12	734667
	CHPF048D2*+G*V90905D**	35,000	25,550	14	12	734893
	CHPF048D2*+G*V950905D**	35,000	25,550	14	12	734697
	CHPF048D2*+G*V951155D**	35,000	25,550	14	12	734851
	CHPF3636B6A*+EEP	35,000	25,550	13	11.5	734707
	CHPF3636B6A*+MBE1200** -1	35,000	25,550	14	12	1038381
	CHPF3642C6A*+EEP	35,000	25,550	13	11.5	734689
	CHPF3642C6A*+MBE1600** -1	35,000	25,550	14	12	1038382
	CHPF3642D6A*+EEP	35,000	25,550	13	11.5	735963
	CHPF3642D6A*+G*V80704B**	35,000	25,550	14	12	734829
	CHPF3642D6A*+G*V80905C**	35,000	25,550	14	12	734751
	CHPF3642D6A*+G*V90905D**	35,000	25,550	14	12	734653
	CHPF3642D6A*+G*V950905D**	35,000	25,550	14	12	734782
	CHPF3642D6A*+G*V951155D**	35,000	25,550	14	12	734810
	CSCF3036N6A*+EEP	35,000	25,550	13	11.5	734768
	CSCF3036N6A*+G*V80704B**	35,000	25,550	14	12	734678
	CSCF3036N6A*+G*V80905C**	35,000	25,550	14	12	734786
	CSCF3036N6A*+G*V90905D**	35,000	25,550	14	12	734675
CSCF3036N6A*+G*V950905D**	35,000	25,550	14	12	734812	
CSCF3036N6A*+G*V951155D**	35,000	25,550	14	12	734779	
CSCF3642*6A*+EEP	35,000	25,550	13	11.5	1002300	
H49F+EEP	35,000	25,550	13	11.5	734758	
H49F+G*V80704B**	35,000	25,550	14	12	734898	
H49F+G*V80905C**	35,000	25,550	14	12	734870	
H49F+G*V90905D**	35,000	25,550	14	12	734883	
H49F+G*V950905D**	35,000	25,550	14	12	734855	
H49F+G*V951155D**	35,000	25,550	14	12	734850	
H60F+EEP	35,000	25,550	13	11.5	1002305	

# PRODUCT SPECIFICATIONS

## PERFORMANCE RATINGS (CONT.)

Outdoor Unit	Indoor Unit	Cooling Capacity				ARI Ref #
		Total	Sensible	SEER <sup>1</sup>	EER <sup>2</sup>	
GSC13 0361B*	ADPF304216A*	35,000	25,550	13	11.5	1038116
	ADPF30421A*	35,000	25,550	13	11.5	736231
	ADPF30421B*	35,000	25,550	13	11.5	1062399
	AEPF303616A*	35,000	25,550	14	12	1038117
	AEPF30361A*	35,000	25,550	14	12	736222
	AEPF30361B*	35,000	25,550	14	12	1062400
	AEPT036-00*-1*	35,000	25,550	14	12	736243
	ARPF048-00B-1*	35,000	25,550	13	11.5	736258
	ARPF364216A*	35,000	25,550	13	11.5	1038118
	ARPF36421A*	35,000	25,550	13	11.5	736239
	ARPF36421B*	35,000	25,550	13	11.5	1062401
	ARPT049-00*-1*	35,000	25,550	13	11.5	736237
	ARUF049-00*-1*	35,000	25,550	13	11.5	736536
	ARUF364216A*	33,600	24,528	13	11.5	1038119
	ARUF36421A*	35,000	25,550	13	11.5	736538
	ARUF36421B*	33,600	24,528	13	11.5	1062402
	AWB36-XX	33,600	24,528	13	11.5	736249
	AWUF36XX1A*	33,600	24,528	13	11.5	736264
	CA*F048*2*+EEP	35,000	25,550	13	11.5	735131
	CA*F048*2*+G*V80704B**	35,000	25,550	14	12	736230
	CA*F048*2*+G*V80905C**	35,000	25,550	14	12	736241
	CA*F048*2*+G*V90905D**	35,000	25,550	14	12	736248
	CA*F048*2*+G*V950905D**	35,000	25,550	14	12	736250
	CA*F048*2*+G*V951155D**	35,000	25,550	14	12	736235
	CA*F048*2*+MBE1600	35,000	25,550	14	12	736254
	CA*F3636*6A*+EEP	35,000	25,550	13	11.5	735128
	CA*F3636*6A*+G*V80704B**	35,000	25,550	14	12	736245
	CA*F3636*6A*+G*V80905C**	35,000	25,550	14	12	736225
	CA*F3636*6A*+G*V90905D**	35,000	25,550	14	12	736232
	CA*F3636*6A*+G*V950905D**	35,000	25,550	14	12	736246
	CA*F3636*6A*+G*V951155D**	35,000	25,550	14	12	736253
	CA*F3636*6A*+MBE1600	35,000	25,550	14	12	736238
	CHPF048D2*+EEP	35,000	25,550	13	11.5	735134
	CHPF048D2*+G*V80704B**	35,000	25,550	14	12	736255
	CHPF048D2*+G*V80905C**	35,000	25,550	14	12	736263
	CHPF048D2*+G*V90905D**	35,000	25,550	14	12	736233
	CHPF048D2*+G*V950905D**	35,000	25,550	14	12	736226
	CHPF048D2*+G*V951155D**	35,000	25,550	14	12	736234
	CHPF3636B6A*+EEP	35,000	25,550	13	11.5	735053
	CHPF3642C6A*+EEP	35,000	25,550	13	11.5	735183
	CHPF3642D6A*+EEP	35,000	25,550	13	11.5	735967
	CHPF3642D6A*+G*V80704B**	35,000	25,550	14	12	736227
	CHPF3642D6A*+G*V80905C**	35,000	25,550	14	12	736242
	CHPF3642D6A*+G*V90905D**	35,000	25,550	14	12	736257
	CHPF3642D6A*+G*V950905D**	35,000	25,550	14	12	736262
	CHPF3642D6A*+G*V951155D**	35,000	25,550	14	12	736236
	CSCF3036N6A*+EEP	35,000	25,550	13	11.5	735205
	CSCF3036N6A*+G*V80704B**	35,000	25,550	14	12	736224
	CSCF3036N6A*+G*V80905C**	35,000	25,550	14	12	736240
	CSCF3036N6A*+G*V90905D**	35,000	25,550	14	12	736259
	CSCF3036N6A*+G*V950905D**	35,000	25,550	14	12	736228
	CSCF3036N6A*+G*V951155D**	35,000	25,550	14	12	736223
	CSCF3642N6A*+EEP	35,000	25,550	13	11.5	1032287
	H49F+EEP	35,000	25,550	13	11.5	735965
H49F+G*V80704B**	35,000	25,550	14	12	736260	
H49F+G*V80905C**	35,000	25,550	14	12	736229	
H49F+G*V90905D**	35,000	25,550	14	12	736256	
H49F+G*V950905D**	35,000	25,550	14	12	736251	
H49F+G*V951155D**	35,000	25,550	14	12	736244	
H60F+EEP	35,000	25,550	13	11.5	1032244	

PERFORMANCE RATINGS (CONT.)

Outdoor Unit	Indoor Unit	Cooling Capacity				ARI Ref #
		Total	Sensible	SEER <sup>1</sup>	EER <sup>2</sup>	
GSC13 0361C*	ADPF304216A*	35,000	25,550	13	11.5	1038120
	ADPF30421A*	35,000	25,550	13	11.5	1032272
	ADPF30421B*	35,000	25,550	13	11.5	1062403
	AEPF30361**	35,000	25,550	14	12	1032273
	AEPF303616A*	35,000	25,550	14	12	1038121
	AEPF30361B*	35,000	25,550	14	12	1062404
	AEPT036-00*-1*	35,000	25,550	14	12	1032274
	ARPF048-00B-1*	35,000	25,550	13	11.5	1032275
	ARPF364216A*	35,000	25,550	13	11.5	1038122
	ARPF36421A*	35,000	25,550	13	11.5	1032276
	ARPF36421B*	35,000	25,550	13	11.5	1062405
	ARPT049-00*-1*	35,000	25,550	13	11.5	1032277
	ARUF049-00*-1*	33,600	24,528	13	11.5	1032294
	ARUF364216A*	33,600	24,528	13	11.5	1038123
	ARUF36421A*	33,600	24,528	13	11.5	1032297
	ARUF36421B*	33,600	24,528	13	11.5	1062406
	AWB36-XX	33,600	24,528	13	11.5	1032283
	AWUF36XX1A*	33,600	24,528	13	11.5	1032284
	CA*F048*2*+EEP	35,000	25,550	13	11.5	1032296
	CA*F048*2*+G*V80704B**	35,000	25,550	14	12	1032281
	CA*F048*2*+G*V80905C**	35,000	25,550	14	12	1032282
	CA*F048*2*+G*V90905D**	35,000	25,550	14	12	1032279
	CA*F048*2*+G*V950905D**	35,000	25,550	14	12	1032280
	CA*F048*2*+G*V951155D**	35,000	25,550	14	12	1032278
	CA*F048*2*+MBE1600**-1	35,000	25,550	14	12	1032295
	CA*F3636*6A*+EEP	35,000	25,550	13	11.5	1032293
	CA*F3636*6A*+G*V80704B**	35,000	25,550	14	12	1032266
	CA*F3636*6A*+G*V80905C**	35,000	25,550	14	12	1032267
	CA*F3636*6A*+G*V90905D**	35,000	25,550	14	12	1032268
	CA*F3636*6A*+G*V950905D**	35,000	25,550	14	12	1032269
	CA*F3636*6A*+G*V951155D**	35,000	25,550	14	12	1032270
	CA*F3636*6A*+MBE1600**-1	35,000	25,550	14	12	1032271
	CHPF048D2*+EEP	35,000	25,550	13	11.5	1032292
	CHPF048D2*+G*V80704B**	35,000	25,550	14	12	1032261
	CHPF048D2*+G*V80905C**	35,000	25,550	14	12	1032262
	CHPF048D2*+G*V90905D**	35,000	25,550	14	12	1032263
	CHPF048D2*+G*V950905D**	35,000	25,550	14	12	1032265
	CHPF048D2*+G*V951155D**	35,000	25,550	14	12	1032264
	CHPF3636B6A*+EEP	35,000	25,550	13	11.5	1032291
	CHPF3642C6A*+EEP	35,000	25,550	13	11.5	1032290
	CHPF3642D6A*+EEP	35,000	25,550	13	11.5	1032289
	CHPF3642D6A*+G*V80704B**	35,000	25,550	14	12	1032260
	CHPF3642D6A*+G*V80905C**	35,000	25,550	14	12	1032259
	CHPF3642D6A*+G*V90905D**	35,000	25,550	14	12	1032257
	CHPF3642D6A*+G*V950905D**	35,000	25,550	14	12	1032258
	CHPF3642D6A*+G*V951155D**	35,000	25,550	14	12	1032254
	CSCF3036N6A*+EEP	35,000	25,550	13	11.5	1032286
	CSCF3036N6A*+G*V80704B**	35,000	25,550	14	12	1032255
	CSCF3036N6A*+G*V80905C**	35,000	25,550	14	12	1032256
	CSCF3036N6A*+G*V90905D**	35,000	25,550	14	12	1032253
CSCF3036N6A*+G*V950905D**	35,000	25,550	14	12	1032251	
CSCF3036N6A*+G*V951155D**	35,000	25,550	14	12	1032252	
CSCF3642N6A*+EEP	35,000	25,550	13	11.5	1032288	
H49F+EEP	35,000	25,550	13	11.5	1032285	
H49F+G*V80704B**	35,000	25,550	14	12	1032248	
H49F+G*V80905C**	35,000	25,550	14	12	1032249	
H49F+G*V90905D**	35,000	25,550	14	12	1032250	
H49F+G*V950905D**	35,000	25,550	14	12	1032246	
H49F+G*V951155D**	35,000	25,550	14	12	1032247	
H60F+EEP	35,000	25,550	13	11.5	1032245	

# PRODUCT SPECIFICATIONS

## PERFORMANCE RATINGS (CONT.)

Outdoor Unit	Indoor Unit	Cooling Capacity				ARI Ref #
		Total	Sensible	SEER <sup>1</sup>	EER <sup>2</sup>	
GSC13 0363A*	ADPF304216A*	35,000	25,550	13	11.5	1038171
	ADPF30421A*	35,000	25,550	13	11.5	735061
	ADPF30421B*	35,000	25,550	13	11.5	1062407
	AEPF303616A*	35,000	25,550	14	11.6	1038170
	AEPF30361A*	35,000	25,550	14	11.6	735042
	AEPF30361B*	35,000	25,550	14	11.6	1062408
	AEPT036-00*-1*	35,000	25,550	14	11.6	735118
	ARPF048-00B-1*	35,000	25,550	13	11.5	735048
	ARPF364216A*	35,000	25,550	13	11.5	1038169
	ARPF36421A*	35,000	25,550	13	11.5	735038
	ARPF36421B*	35,000	25,550	13	11.5	1062409
	ARPT049-00*-1*	35,000	25,550	13	11.5	735181
	CA*F048*2*+EEP	35,000	25,550	13	11.5	735113
	CA*F3636*6A*+EEP	35,000	25,550	13	11.5	735184
	CHPF048D2*+EEP	35,000	25,550	13	11.5	735064
	CHPF3636B6A*+EEP	35,000	25,550	13	11.5	735246
	CHPF3642C6A*+EEP	35,000	25,550	13	11.5	735126
	CHPF3642D6A*+EEP	35,000	25,550	13	11.5	735966
	CSCF3036N6A*+EEP	35,000	25,550	13	11.5	735236
	H49F+EEP	35,000	25,550	13	11.5	735111
GSC13 0421A*	ADPF304216A*	40,500	30,375	13	11.5	1038124
	ADPF30421A*	40,500	30,375	13	11.5	734788
	ADPF30421B*	40,500	30,375	13	11.5	1062410
	AEPF426016A*	41,000	30,750	14	12	1038125
	AEPF42601A*	41,000	30,750	14	12	734878
	AEPF42601B*	41,000	30,750	14	12	1062411
	AEPT060-00*-1*	41,000	30,750	14	12	734783
	ARPF048-00B-1*	40,500	30,375	13	11.5	734861
	ARPF364216A*	40,500	30,375	13	11.5	1038126
	ARPF36421A*	40,500	30,375	13	11.5	734843
	ARPF36421B*	40,500	30,375	13	11.5	1062412
	ARPT049-00*-1*	40,500	30,375	13	11.5	734833
	ARUF049-00*-1*	40,500	30,375	13	11.5	734650
	ARUF364216A*	40,500	30,375	13	11.5	1038127
	ARUF36421A*	40,500	30,375	13	11.5	734857
	ARUF36421B*	40,500	30,375	13	11.5	1062413
	ARUF486016A*	41,500	31,125	13	11.5	1038142
	ARUF48601A*	41,500	31,125	13	11.5	1038141
	ARUF48601B*	41,500	31,125	13	11.5	1062414
	CA*F060*2*+EEP	40,500	30,375	13	11.5	734676
	CA*F060*2*+MBE1600	40,500	30,375	14	12	734897
	CA*F061*2*+G*V80905C**	41,500	31,125	14	12	734670
	CA*F061*2*+G*V81155C**	41,500	31,125	14	12	734681
	CA*F061*2*+G*V90905D**	41,500	31,125	13.5	11.8	734679
	CA*F061*2*+G*V950905D**	41,500	31,125	13.5	11.8	734753
	CA*F061*2*+G*V951155D**	41,500	31,125	13.5	11.8	734776
	CA*F3642*6A*+EEP	40,500	30,375	13	11.5	734694
	CA*F3642*6A*+MBE1600	40,500	30,375	14	12	734702
	CA*F4860*6A*+G*V80905C**	41,500	31,125	14	12	734896
	CA*F4860*6A*+G*V81155C**	41,500	31,125	14	12	734789
	CA*F4860*6A*+G*V90905D**	41,500	31,125	13.5	11.8	734665
	CA*F4860*6A*+G*V950905D**	41,500	31,125	13.5	11.8	734811
	CA*F4860*6A*+G*V951155D**	41,500	31,125	13.5	11.8	734864
	CAPF061*2*+EEP	41,000	30,750	13	11.5	1002303
	CAPF4860*6A*+EEP	41,000	30,750	13	11.5	1002304
	CHPF048D2*+EEP	40,500	30,375	13	11.5	734740
	CHPF060D2*+EEP	41,000	30,750	13	11.5	1002301
	CHPF060D2*+G*V81155C**	41,500	31,125	14	12	734868
	CHPF060D2*+G*V90905D**	41,500	31,125	13.5	11.8	734862

See Notes on Page 16.

PERFORMANCE RATINGS (CONT.)

Outdoor Unit	Indoor Unit	Cooling Capacity				ARI Ref #
		Total	Sensible	SEER <sup>1</sup>	EER <sup>2</sup>	
GSC13 0421A (cont.)	CHPF060D2*+G*V951155D**	41,500	31,125	13.5	11.8	734677
	CHPF3642C6A*+EEP	40,500	30,375	13	11.5	734725
	CHPF3642D6A*+EEP	40,500	30,375	13	11.5	734682
	CHPF4860D6A*+EEP	41,000	30,750	13	11.5	1002302
	CHPF4860D6A*+G*V81155C**	41,500	31,125	14	12	734652
	CHPF4860D6A*+G*V90905D**	41,500	31,125	13.5	11.8	734838
	CHPF4860D6A*+G*V951155D**	41,500	31,125	13.5	11.8	734759
	CSCF3642N6A*+EEP	41,500	31,125	13	11.5	734769
	CSCF4860N6A*+G*V81155C**	41,500	31,125	14	12	734800
	CSCF4860N6A*+G*V90905D**	41,500	31,125	13.5	11.8	734763
	CSCF4860N6A*+G*V951155D**	41,500	31,125	13.5	11.8	734749
	H60F+EEP	41,500	31,125	13	11.5	734872
	H61F+EEP	42,000	31,500	13	11.5	1038150
	H61F+G*V81155C**	41,500	31,125	14	12	734684
	H61F+G*V90905D**	41,500	31,125	13.5	11.8	734771
H61F+G*V951155D**	41,500	31,125	13.5	11.8	734683	
GSC13 0481A*	ADPF486016A*	45,500	33,670	13	11.5	1038128
	ADPF48601A*	45,500	33,670	13	11.5	734791
	ADPF48601B*	45,500	33,670	13	11.5	1062415
	AEPF426016A*	45,500	33,670	14	12	1038129
	AEPF42601A*	45,500	33,670	14	12	734696
	AEPF42601B*	45,500	33,670	14	12	1062416
	AEPT060-00*-1*	45,500	33,670	14	12	734757
	ARPF060-00B-1*	45,500	33,670	13	11.5	734756
	ARPF486016A*	45,500	33,670	13	11.5	1038130
	ARPF48601A*	45,500	33,670	13	11.5	734813
	ARPF48601B*	45,500	33,670	13	11.5	1062417
	ARPT061-00*-1*	45,500	33,670	13	11.5	734853
	ARUF061-00*-1*	45,500	33,670	13	11.5	734703
	ARUF486016A*	45,500	33,670	13	11.5	1038131
	ARUF48601A*	45,500	33,670	13	11.5	734772
	ARUF48601B*	45,500	33,670	13	11.5	1062418
	CA*F061*2*+EEP	45,500	33,670	13	11.5	734699
	CA*F061*2*+G*V80905C**	45,500	33,670	13.5	11.8	734854
	CA*F061*2*+G*V81155C**	45,500	33,670	13.5	11.8	734881
	CA*F061*2*+G*V90905D**	45,500	33,670	13.5	11.8	734719
	CA*F061*2*+G*V950905D**	45,500	33,670	13.5	11.8	734734
	CA*F061*2*+G*V951155D**	45,500	33,670	13.5	11.8	734720
	CA*F061*2*+MBE2000	45,500	33,670	14	12	734712
	CA*F4860*6A*+EEP	45,500	33,670	13	11.5	734828
	CA*F4860*6A*+G*V80905C**	45,500	33,670	13.5	11.8	734663
	CA*F4860*6A*+G*V81155C**	45,500	33,670	13.5	11.8	734750
	CA*F4860*6A*+G*V90905D**	45,500	33,670	13.5	11.8	734733
	CA*F4860*6A*+G*V950905D**	45,500	33,670	13.5	11.8	734822
	CA*F4860*6A*+G*V951155D**	45,500	33,670	13.5	11.8	734796
	CA*F4860*6A*+MBE2000	45,500	33,670	14	12	734729
	CHPF060D2*+EEP	45,500	33,670	13	11.5	734825
	CHPF060D2*+G*V80905C**	45,500	33,670	13.5	11.8	734669
	CHPF060D2*+G*V81155C**	45,500	33,670	13.5	11.8	734808
	CHPF060D2*+G*V90905D**	45,500	33,670	13.5	11.8	734899
	CHPF060D2*+G*V950905D**	45,500	33,670	13.5	11.8	734839
	CHPF060D2*+G*V951155D**	45,500	33,670	13.5	11.8	736537
	CHPF4860D6A*+EEP	45,500	33,670	13	11.5	734877
	CHPF4860D6A*+G*V80905C**	45,500	33,670	13.5	11.8	734688
	CHPF4860D6A*+G*V81155C**	45,500	33,670	13.5	11.8	734869
	CHPF4860D6A*+G*V90905D**	45,500	33,670	13.5	11.8	734708
CHPF4860D6A*+G*V950905D**	45,500	33,670	13.5	11.8	734713	

<sup>1</sup> Seasonal Energy Efficiency Ratio  
<sup>2</sup> Energy Efficiency Ratio @ 80 °F/67 °F Inside - 95 °F  
 See Notes on Page 16.

# PRODUCT SPECIFICATIONS

## PERFORMANCE RATINGS (CONT.)

Outdoor Unit	Indoor Unit	Cooling Capacity				ARI Ref #
		Total	Sensible	SEER <sup>1</sup>	EER <sup>2</sup>	
GSC13 0481A* (cont.)	CHPF4860D6A*+G*V951155D**	45,500	33,670	13.5	11.8	736533
	CSCF4860N6A*+EEP	45,500	33,670	13	11.5	734885
	CSCF4860N6A*+G*V80905C**	45,500	33,670	13.5	11.8	734780
	CSCF4860N6A*+G*V81155C**	45,500	33,670	13.5	11.8	734778
	CSCF4860N6A*+G*V90905D**	45,500	33,670	13.5	11.8	734716
	CSCF4860N6A*+G*V950905D**	45,500	33,670	13.5	11.8	734655
	CSCF4860N6A*+G*V951155D**	45,500	33,670	13.5	11.8	734721
	H61F+EEP	45,500	33,670	13	11.5	734735
	H61F+G*V80905C**	45,500	33,670	13.5	11.8	734792
	H61F+G*V81155C**	45,500	33,670	13.5	11.8	734715
	H61F+G*V90905D**	45,500	33,670	13.5	11.8	734797
H61F+G*V950905D**	45,500	33,670	13.5	11.8	734834	
H61F+G*V951155D**	45,500	33,670	13.5	11.8	734777	
GSC13 0483A*	ADPF486016A*	45,500	33,670	13	11.5	1038168
	ADPF48601A*	45,500	33,670	13	11.5	872332
	ADPF48601B*	45,500	33,670	13	11.5	1062419
	AEPF426016A*	45,500	33,670	14	11.6	1038167
	AEPF42601A*	45,500	33,670	14	11.6	872366
	AEPF42601B*	45,500	33,670	14	11.6	1062420
	AEPT060-00*-1*	45,500	33,670	14	11.6	872400
	ARPF060-00B-1*	45,500	33,670	13	11.5	872345
	ARPF486016A*	45,500	33,670	13	11.5	1038165
	ARPF48601A*	45,500	33,670	13	11.5	872351
	ARPF48601B*	45,500	33,670	13	11.5	1062421
	ARPT061-00*-1*	45,500	33,670	13	11.5	872223
	ARUF061-00*-1*	45,500	33,670	13	11.5	872220
	ARUF486016A*	45,500	33,670	13	11.5	1038166
	ARUF48601A*	45,500	33,670	13	11.5	872282
	ARUF48601B*	45,500	33,670	13	11.5	1062422
	CA*F061*2*+EEP	45,500	33,670	13	11.5	869440
	CA*F4860*6A*+EEP	45,500	33,670	13	11.5	869438
	CHPF060D2*+EEP	45,500	33,670	13	11.5	869450
	CHPF4860D6A*+EEP	45,500	33,670	13	11.5	869456
CSCF4860N6A*+EEP	45,500	33,670	13	11.5	869457	
H61F+EEP	45,500	33,670	13	11.5	869462	
GSC13 0484A*	ADPF486016A*	45,500	33,670	13	11.5	1038164
	ADPF48601A*	45,500	33,670	13	11.5	872367
	ADPF48601B*	45,500	33,670	13	11.5	1062440
	AEPF426016A*	45,500	33,670	14	11.6	1038163
	AEPF42601A*	45,500	33,670	14	11.6	872388
	AEPF42601B*	45,500	33,670	14	11.6	1062441
	AEPT060-00*-1*	45,500	33,670	14	11.6	872398
	ARPF060-00B-1*	45,500	33,670	13	11.5	872371
	ARPF486016A*	45,500	33,670	13	11.5	1038162
	ARPF48601A*	45,500	33,670	13	11.5	872337
	ARPF48601B*	45,500	33,670	13	11.5	1062442
	ARPT061-00*-1*	45,500	33,670	13	11.5	872300
	ARUF061-00*-1*	45,500	33,670	13	11.5	872276
	ARUF486016A*	45,500	33,670	13	11.5	1038161
	ARUF48601A*	45,500	33,670	13	11.5	872232
	ARUF48601B*	45,500	33,670	13	11.5	1062443
	CA*F061*2*+EEP	45,500	33,670	13	11.5	869474
	CA*F4860*6A*+EEP	45,500	33,670	13	11.5	869464
	CHPF060D2*+EEP	45,500	33,670	13	11.5	869467
	CHPF4860D6A*+EEP	45,500	33,670	13	11.5	869465
CSCF4860N6A*+EEP	45,500	33,670	13	11.5	869454	
H61F+EEP	45,500	33,670	13	11.5	869461	

<sup>1</sup> Seasonal Energy Efficiency Ratio

<sup>2</sup> Energy Efficiency Ratio @ 80 °F/67 °F Inside - 95 °F

See Notes on Page 15.

PERFORMANCE RATINGS (CONT.)

Outdoor Unit	Indoor Unit	Cooling Capacity				ARI Ref #
		Total	Sensible	SEER <sup>1</sup>	EER <sup>2</sup>	
GSC13 0601B*	ADPF486016A*	57,000	41,040	13	11.5	1038132
	ADPF48601A*	57,000	41,040	13	11.5	734731
	ADPF48601B*	57,000	41,040	13	11.5	1062423
	AEPF426016A*	57,000	41,040	13.5	11.8	1038133
	AEPF42601A*	57,000	41,040	13.5	11.8	734754
	AEPF42601B*	57,000	41,040	13.5	11.8	1062424
	AEPT060-00*-1*	57,000	41,040	13.5	11.8	734686
	ARPF060-00B-1*	57,000	41,040	13	11.5	734901
	ARPF486016A*	57,000	41,040	13	11.5	1038134
	ARPF48601A*	57,000	41,040	13	11.5	734820
	ARPF48601B*	57,000	41,040	13	11.5	1062425
	ARPT061-00*-1*	57,000	41,040	13	11.5	734745
	ARUF061-00*-1*	57,000	41,040	13	11.5	734723
	ARUF486016A*	57,000	41,040	13	11.5	1038135
	ARUF48601A*	57,000	41,040	13	11.5	734858
	ARUF48601B*	57,000	41,040	13	11.5	1062426
	CA*F061*2*+EEP	57,000	41,040	13	11.5	734866
	CA*F061*2*+G*V80905C**	57,000	41,040	13.3	11.7	734673
	CA*F061*2*+G*V81155C**	57,000	41,040	13.3	11.7	734852
	CA*F061*2*+G*V90905D**	57,000	41,040	13.3	11.7	734874
	CA*F061*2*+MBE2000	57,000	41,040	13.5	11.8	734849
	CA*F4860*6A*+EEP	57,000	41,040	13	11.5	734741
	CA*F4860*6A*+G*V80905C**	57,000	41,040	13.3	11.7	734755
	CA*F4860*6A*+G*V81155C**	57,000	41,040	13.3	11.7	734710
	CA*F4860*6A*+G*V90905D**	57,000	41,040	13.3	11.7	734685
	CA*F4860*6A*+MBE2000	57,000	41,040	13.5	11.8	734658
	CHPF060D2*+EEP	57,000	41,040	13	11.5	734709
	CHPF060D2*+G*V80905C**	57,000	41,040	13.3	11.7	734847
	CHPF060D2*+G*V81155C**	57,000	41,040	13.3	11.7	734766
	CHPF060D2*+G*V90905D**	57,000	41,040	13.3	11.7	734706
	CHPF4860D6A*+EEP	57,000	41,040	13	11.5	734701
	CHPF4860D6A*+G*V80905C**	57,000	41,040	13.3	11.7	734790
	CHPF4860D6A*+G*V81155C**	57,000	41,040	13.3	11.7	734662
	CHPF4860D6A*+G*V90905D**	57,000	41,040	13.3	11.7	734832
	CSCF4860N6A*+EEP	56,000	40,320	13	11.5	734860
	CSCF4860N6A*+G*V80905C**	56,000	40,320	13.3	11.7	734770
	CSCF4860N6A*+G*V81155C**	56,000	40,320	13.3	11.7	734674
	CSCF4860N6A*+G*V90905D**	56,000	40,320	13.3	11.7	735964
	H61F+EEP	56,000	40,320	13	11.5	734711
	H61F+G*V80905C**	56,000	40,320	13.3	11.7	734752
H61F+G*V81155C**	56,000	40,320	13.3	11.7	734882	
H61F+G*V90905D**	56,000	40,320	13.3	11.7	734805	

<sup>1</sup> Seasonal Energy Efficiency Ratio  
<sup>2</sup> Energy Efficiency Ratio @ 80 °F/67 °F Inside - 95 °F

Notes:

- When matching the outdoor unit to the indoor unit, use the piston supplied with the outdoor unit or that specified on the piston kit chart supplied with the indoor unit.
- XX of a model designates Electric Heat kilowatts.
- EEP: Order from Service Dept. Part No. B13707-38 or new Solid State Board B13707-35S. Part No. B13707-38 is not interchangeable with B13707-35S. The Goodman Gas Furnace contains the EEP cooling time delay.

# PRODUCT SPECIFICATIONS

## PERFORMANCE RATINGS (CONT.)

Outdoor Unit	Indoor Unit	Cooling Capacity				ARI Ref #
		Total	Sensible	SEER <sup>1</sup>	EER <sup>2</sup>	
GSC13 0603A*	ADPF486016A*	57,000	41,040	13	11.5	1038160
	ADPF48601A*	57,000	41,040	13	11.5	872325
	ADPF48601B*	57,000	41,040	13	11.5	1062427
	ARPF060-00B-1*	57,000	41,040	13	11.5	872227
	ARPF486016A*	57,000	41,040	13	11.5	1038159
	ARPF48601A*	57,000	41,040	13	11.5	872404
	ARPF48601B*	57,000	41,040	13	11.5	1062428
	ARPT061-00*-1*	57,000	41,040	13	11.5	872358
	ARUF061-00*-1*	57,000	41,040	13	11.5	872297
	ARUF486016A*	57,000	41,040	13	11.5	1038158
	ARUF48601A*	57,000	41,040	13	11.5	872380
	ARUF48601B*	57,000	41,040	13	11.5	1062429
	CA*F061*2*+EEP	57,000	41,040	13	11.5	869444
	CA*F4860*6A*+EEP	57,000	41,040	13	11.5	869460
	CHPF060D2*+EEP	57,000	41,040	13	11.5	869473
	CHPF4860D6A*+EEP	57,000	41,040	13	11.5	869471
	CSCF4860N6A*+EEP	56,000	40,320	13	11.5	869449
	H61F+EEP	56,000	40,320	13	11.5	869430
	GSC13 0604A*	ADPF486016A*	57,000	41,040	13	11.5
ADPF48601A*		57,000	41,040	13	11.5	872286
ADPF48601B*		57,000	41,040	13	11.5	1062444
ARPF060-00B-1*		57,000	41,040	13	11.5	872245
ARPF486016A*		57,000	41,040	13	11.5	1038156
ARPF48601A*		57,000	41,040	13	11.5	872248
ARPF48601B*		57,000	41,040	13	11.5	1062445
ARPT061-00*-1*		57,000	41,040	13	11.5	872250
ARUF061-00*-1*		57,000	41,040	13	11.5	872389
ARUF486016A*		57,000	41,040	13	11.5	1038155
ARUF48601A*		57,000	41,040	13	11.5	872236
ARUF48601B*		57,000	41,040	13	11.5	1062439
CA*F061*2*+EEP		57,000	41,040	13	11.5	869432
CA*F4860*6A*+EEP		57,000	41,040	13	11.5	869475
CHPF060D2*+EEP		57,000	41,040	13	11.5	869448
CHPF4860D6A*+EEP		57,000	41,040	13	11.5	869437
CSCF4860N6A*+EEP		56,000	40,320	13	11.5	869470
H61F+EEP		56,000	40,320	13	11.5	869459

<sup>1</sup> Seasonal Energy Efficiency Ratio

<sup>2</sup> Energy Efficiency Ratio @ 80 °F/67 °F Inside - 95 °F

**Notes:**

- When matching the outdoor unit to the indoor unit, use the piston supplied with the outdoor unit or that specified on the piston kit chart supplied with the indoor unit.
- XX of a model designates Electric Heat kilowatts.
- EEP: Order from Service Dept. Part No. B13707-38 or new Solid State Board B13707-35S. Part No. B13707-38 is not interchangeable with B13707-35S. The Goodman Gas Furnace contains the EEP cooling time delay.



**Air Conditioning & Heating**

*Goodman Manufacturing Company, L.P., reserves the right to discontinue, or change at any time, specifications or designs without notice or without incurring obligations.*

*Copyright © 2006 • Goodman Manufacturing Company, L.P. • Houston, Texas  
Goodman® brand products are proudly made in the USA.  
Printed in the USA.*